

AXIS C3003-E Network Horn Speaker

Clear and simple

AXIS C3003-E Network Horn Speaker is a simple-to-install outdoor loudspeaker that provides clear, long-range speech for remote speaking in live video surveillance. Audio can be manually or automatically triggered in response to an alarm, and deter unwanted activity through pre-installed or uploaded audio files. The loudspeaker has an integrated amplifier and combines low power consumption with high sound pressure. AXIS C3003-E integrates easily with SIP (Session Initiation Protocol) Voice over IP (VoIP) systems and video management software (VMS) supporting audio. Several speakers can be connected in a zone with synchronized audio using only one IP address for the leader speaker.

- > **Simple installation with PoE**
- > **Easy VMS integration**
- > **Supports open standards – VAPIX, ACAP, SIP**
- > **Reliable Auto Speaker Test**



AXIS C3003-E Network Horn Speaker

Audio		General	
Audio streaming	One-way/two-way ^a (mono)	Casing	Impact-resistant aluminum, IP66-, IP67- and NEMA 4X-rated. For repainting instructions and impact on warranty, contact your Axis partner
Audio compression	G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Axis μ -law 16 kHz, WAV, MP3 in mono/stereo from 64 kbps to 320 kbps. Constant and variable bit rate. Sampling rate from 8 kHz up to 48 kHz.	Memory	256 MB RAM, 256 MB Flash
Audio input/output	Built-in microphone (can be disabled mechanically)	Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 (max. 12.95 W)
Built-in microphone specification	50 Hz - 16 kHz	Connectors	RJ45 10BASE-T/100BASE-TX PoE
Speaker		Operating conditions	-20°C to 50 °C (-4 °F to 122 °F) Humidity 10-100% RH (condensing)
Max sound pressure level	>121 dB	Approvals	EN 55022 Class B, EN 61000-6-1, EN 61000-6-2, EN 55024, EN 50121-4, IEC 62236-4, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, C-tick AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24, IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-64, IEC 60068-2-78, IEC/EN 60529 IP66, IEC/EN 60529 IP67, NEMA 250 Type 4X
Frequency response	280 Hz - 12.5 kHz	Dimensions	Without bracket: 164 x 225 x 250 mm (6 1/2 x 8 7/8 x 9 7/8 in.) With bracket: 164 x 225 x 305 mm (6 1/2 x 8 7/8 x 12 in.)
Coverage pattern	70° horizontal by 100° vertical (at 2 kHz)	Weight	1.3 kg (2.9 lb.)
Amplifier		Included accessories	Installation Guide, AVHS Authentication Key, AXIS Camera Station license key, AXIS Connector Guard A, Cable shoe
Amplifier description	Built-in 7 W Class D amplifier	Optional accessories	AXIS T91A47 Pole Mount, AXIS T91C67 Pole Mount, Cable Gland M20x1.5, RJ45, Cable Gland A M20, AXIS Power over Ethernet Midspans
Network		Video management software	AXIS Camera Station and video management software from Axis' Application Development Partners (not included)
Security	Password protection, IP address filtering, HTTPS ^b encryption, IEEE 802.1X ^b network access control, Digest authentication, User access log	Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese
Supported protocols	IPv4/v6, HTTP, HTTPS ^b , SIP, SSL/TLS ^b , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP TM , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, TCP, UDP, IGMP, ICMP, DHCP, ARP, SOCKS, SSH	Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see www.axis.com/warranty
System integration		a. This product supports two-way audio for sending audio to the speaker and receiving audio from the microphone. The product does not support two-way communication for conversations with speaker operators. b. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com). c. Audio synchronization with IPv4 only.	
Application Programming Interface	Open API for software integration, including VAPIX [®] , AXIS Video Hosting System (AVHS) with One-click Connection, AXIS Camera Application Platform (ACAP).	Environmental responsibility:	
Audio synchronization	Built-in audio synchronization ^c for up to 50 speakers with unicast and hundreds of speakers with multicast. No additional speaker management software or hardware required.	www.axis.com/environmental-responsibility	
Voice announcement	Up to 50 pre-recorded voice announcements. Voice announcement through built-in SIP support for connection to any IP telephone /VoIP system and VAPIX support.		
VoIP	Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX. Tested with: SIP client such as Cisco, Bria and Grandstream and PBX suppliers such as Cisco and Asterisk. Supported SIP features: secondary SIP server, IPv6, SRTP, SIPS, SIP TLS, DTMF (RFC2976 and RFC2833), NAT (ICE, STUN, TURN) Supported codecs: PCMU, PCMA, opus, L16/16000, L16/8000, speex/8000, speex/16000, G.726-32		
Intelligent audio	Auto Speaker Test		
Event triggers	Virtual inputs Call: DTMF, State changes, AXIS Camera Application Platform (ACAP)		
Event actions	File upload: HTTP, network share and email Notification: email, HTTP and TCP Play audio clip Send Auto Speaker Test Send SNMP trap Status LED		
Built-in installation aids	Test tone verification and identification		
Functional monitoring	Auto Speaker Test, Connection verification, Built-in system logging		